

Supporting Information

Identification of tobacco types and cigarette brands using an electronic nose based on conductive polymer/porphyrin composite sensors

**C. Henrique A. Esteves^{a,§}, Bernardo A. Iglesias^{a,d}, Takuji Ogawa^b, Koiti Araki^a,
Lucélia Hoehne^c, Jonas Gruber^{a,*}**

^a Departamento de Química Fundamental, Instituto de Química, Universidade de São Paulo, Avenida Professor Lineu Prestes, 748, 05508-000 São Paulo, SP, Brazil.

^b Osaka University, Graduate School of Science, Department of Chemistry, Toyonaka, Osaka, 560 0043, Japan

^c Centro Universitário UNIVATES, Av. Avelino Talini 171, 95900-000, Lajeado, RS, Brazil.

^d Departamento de Química, Universidade Federal de Santa Maria, Avenida Roraima, 1000, 97105-900 Santa Maria, RS, Brazil.

*Corresponding author. Tel.: +55 11 3091-1103

E-mail address: jogruber@iq.usp.br (J. Gruber).

§ Current address:

Departamento de Farmácia, Faculdade de Ciências Farmacêuticas, Universidade de São Paulo, 05508-000 São Paulo, SP, Brazil.

1. Conductance output for cigarette brands




Figure S1: Conductance output for M1 (Marlboro Silver).




Figure S2: Conductance output for M2 (Marlboro Gold).




Figure S3: Conductance output for M3 (Marlboro).




Figure S4: Conductance output for M4 (Marlboro Blue Ice).




Figure S5: Conductance output for M5 (Marlboro Fresh Mint).




Figure S6: Conductance output for S1 (Dunhill).




Figure S7: Conductance output for S2 (Lucky Strike).




Figure S8: Conductance output for S3 (Derby).