Supporting Information for

Waterborne Epoxy Resin/Polydopamine Modified Zirconium Phosphate Nanocomposite for Anticorrosive Coating

Xinxin Sheng[†], Ruibin $Mo^{\dagger,\$}$, Yue Ma^{\dagger} , Xinya Zhang[§], Li Zhang[†]*, Hua $Wu^{\ddagger*}$

 [†] Guangdong Provincial Key Laboratory of Functional Soft Condensed Matter, School of Materials and Energy, Guangdong University of Technology, Guangzhou, 510006 China.

§ School of Chemistry and Chemical Engineering, South China University of Technology, Guangzhou, 510641 China.

‡ Institute for Chemical and Bioengineering, Department of Chemistry and Applied Biosciences, ETH Zurich, 8093 Zurich, Switzerland.

* Corresponding authors: Email: <u>lizhang@gdut.edu.cn</u> (LZ); <u>hua.wu@chem.ethz.ch</u> (HW)



Figure S1. The AFM image and its corresponding analysis chart used to measure the geometric parameters of ZrP (a, c) and PDA-ZrP (b, d).



Figure S2. The TEM images of ZrP (a, b) and PDA-ZrP (c, d).



Figure S3. The TEM images of PDA-ZrP waterborne epoxy coatings.



Figure S4. The DSC curves of 0% PDA-ZrP, 0.2% PDA-ZrP, 0.5% PDA-ZrP and 1.0% PDA-ZrP.

3