Supporting Information

Photo-polymerization of Acrylated Epoxidized Soybean Oil: A Photo-calorimetry Based Kinetic Study

Adhimoolam Bakthavachalam Kousaalya^{$\delta,\#, \delta$}, Beshah Ayalew^{δ}, Srikanth Pilla^{$\delta,\#,\&,\delta^*$},

^{\$}Department of Automotive Engineering, Clemson University, Greenville, SC, USA

[#]Clemson Composites Center, Clemson University, Greenville, SC, USA

*Department of Materials Science and Engineering, Clemson University, Clemson, SC, USA

^bDepartment of Mechanical Engineering, Clemson University, Clemson, SC, USA
¹Present address: Department of Chemical Engineering, Rowan University, Glassboro, NJ, USA
*Corresponding author: spilla@clemson.edu; Tel: 1-864-283-7216

This document contains 3 pages:

Figures	Page
Figure S1. Heat flow as a function of time during photo-curing of AESO at varying photo-initiator concentration, intensity and temperature for two different photo-initiators in the low-intensity regime	S2
Figure S2: Heat flow as a function of time during photo-curing of AESO at varying photo-initiator concentration, intensity and temperature for two different photo-initiators in the medium-intensity regime	S2
Figure S3: ¹ H NMR Spectra of Acrylated Epoxidized Soybean oil	S3



Figure S1: Heat flow as a function of time during photo-curing of AESO at varying photoinitiator concentration, intensity and temperature for two different photo-initiators in the low-

intensity regime



Figure S2: Heat flow as a function of time during photo-curing of AESO at varying photoinitiator concentration, intensity and temperature for two different photo-initiators in the medium-intensity regime



Figure S3: ¹H NMR Spectra of Acrylated Epoxidized Soybean oil