

Supporting Information

Improvement of Ultrafiltration for Treatment of Phosphorus-Containing Water by a Lanthanum-Modified Aminated Polyacrylonitrile Membrane

Kok Yuen Koh^a, Sui Zhang^{b*}, Jiaping Paul Chen^{a*}

^a*Department of Civil and Environmental Engineering, National University of Singapore, 10 Kent Ridge Crescent, Singapore 119260, Singapore*

^b*Department of Chemical and Biomolecular Engineering, National University of Singapore, Singapore 117576*

Table of content

Adsorption kinetic models' constants Table S1

Adsorption isotherm models' constants Table S2

Regeneration study of PAN-NH₂-La0.3 membrane Table S3

pH changes after adsorption of phosphate by PAN-NH₂-La0.3 membrane Fig. S1

La leakage from pristine and regenerated membrane during dead-end filtration Fig. S2

High resolution P 2p XPS spectrum after adsorption Fig. S3

***Corresponding Author:** S. Zhang (Email: chezhasui@nus.edu.sg, Tel: +65 65163781), J. Paul Chen (Email: paulchen@nus.edu.sg, jpaulchen@gatech.edu, Tel: +65 65168092)

Table S1. Kinetics model constants

Pseudo-first-order equation			Pseudo-second-order equation			Intraparticle diffusion equation		
q _e (mg/g)	k ₁ (h ⁻¹)	r ²	q _e (mg/g)	k ₂ (g/mg.h)	r ²	k _{id} (mg.g ⁻¹ .h ^{-1/2})	α (mg.g ⁻¹)	r ²
56.55	0.35	0.9931	74.07	5.25E-03	0.9878	26.13	-5.81	0.9942

Table S2. Adsorption Isotherms' constants

pH	Langmuir			Freundlich		
	q _{max} (mg.g ⁻¹)	K _L (L.mg ⁻¹)	r ²	K _f (mg.g ⁻¹)(L.mg ⁻¹) ^{1/n}	n	r ²
5	50.00	2.22	0.9985	31.49	10.25	0.2597
7	44.64	0.97	0.9957	26.45	7.24	0.6967

Table S3. Regeneration study of membrane. Volume: 100 ml; contact time: 24 h

Concentration, M (Regenerant)	Temperature (°C)	Recovery of phosphate (%) ^b	Capacity retained (%) ^c
0.01 (NaOH)	rt ^a	3.96±0.20	29.11±1.73
0.1 (NaOH)	rt	6.76±0.26	28.37±5.19
1 (NaOH)	rt	35.62±2.96	47.00±0.47
1 (NaOH)	60	47.48±0.71	-
1 (NaHCO ₃)	rt	14.06±0.78	35.74±6.44
1 (NaHCO ₃)	60	28.89±0.80	48.40±2.96
0.1 (NaOH)+ 1 (NaHCO ₃)	60	45.15±0.82	64.74±3.31
2 (NaHCO ₃)	60	67.55±1.57	87.23±5.55
0.1 (NaOH)+ 2 (NaHCO ₃)	60	66.44±5.57	83.81±7.88

^aroom temperature^bamount of phosphate detected in regenerant solution over amount of phosphate adsorbed^aadsorption capacity of phosphate in second cycle over that in first cycle




Figure S1. Changes of pH after adsorption




Figure S2. La leakage during filtration study




Figure S3. High resolution P 2p spectrum of PAN-NH₂-La0.3 membrane after adsorption