Supporting Information for

Effects of Side-Chain Interdigitation on Stability: An Environmentally, Electrically, and Thermally Stable Semiconducting Polymer

Danbi Choi $^{(a)}$, Ban-Seok Jeong $^{(b)}$, Byungcheol Ahn $^{(c)}$, Dae Sung Chung $^{(a)}$, Ki-Min Lim $^{(b)}$, Se Hyun Kim $^{(a)}$, Seon Uk Park $^{(a)}$, Moonhor Ree $^{(c)*}$, Jaejung Ko $^{(b)*}$, Chan Eon Park $^{(a)*}$

Tel: +82-54-279-2269 (CEP), +82-41-860-1337 (JK), +82-54-279-2120 (MR) Fax: +82-54-279-8298 (CEP), +82-41-867-5396 (JK), +82-54-279-3399 (MR)

E-mail: cep@postech.edu (CEP), jko@korea.ac.kr (JK), ree@postech.edu (MR)

⁽a) Polymer Research Institute, Department of Chemical Engineering, Pohang University of Science and Technology, Pohang, 790-784, Korea;

⁽b) Department of New Materials Chemistry, Korea University, Jochiwon, Chungnam 339-700 (Korea);

⁽c) Department of Chemistry, Division of Advanced Materials Science, Center for Electro-Photo Behaviors in Advanced Molecular Systems, Pohang Accelerator Laboratory, Polymer Research Institute, and BK School of Molecular Science, Pohang University of Science and Technology, Pohang, 790-794, Korea

 $[\]boldsymbol{*}$ To whom all correspondence should be addressed.




Figure S1. ¹H NMR spectrum of the PDHTT




Figure S2. (a) UV-Vis absorption spectra and (b) cyclic voltammetry (vs Ag/AgCl) of the PDHTT film.




Figure S3. I_D - V_G transfer characteristics of PDHTT-based OTFTs in the saturation regime $(V_D = -80 \text{ V})$.




Figure S4. (a) $I_D^{1/2}$ - V_G , (b) I_D - V_G transfer characteristics of the PDHTT OTFTs at various gate voltages.




Figure S5. (a) TGA and (b) DSC analyses of PDHTT film.